

Boomlift / Manlift

Used Boom Lift Maryland - The boom lift is one of the most popular kinds of aerial machinery. Also referred to as elevating work platforms, aerial devices, cherry pickers, mobile elevating work platforms and aerial work platforms, boom lifts are capable of completing jobs at higher elevations easily and efficiently. Warehouses, companies, contractors and retail operations and more rely on boom lifts on a daily basis. Keeping workers safe as they access conditions in a higher altitude is priceless. There are numerous models of boom lifts available in the industry. A single operator can control a variety of boom lift models. This machine is popular for harvesting fruit in locations such as orchards that historically relied on climbing dangerous ladders. Since ladders require even, solid ground for setting them up safely, they can be unreliable in the agricultural industry. Relying on a boom lift is an easier and safer way to reach tree tops. Gaining Access Over Obstacles Boom lifts make working over top of obstacle much easier as many models have been engineered to travel up and over items. This equipment is used in numerous industries including installing telephone poles and lines, maintaining overhead cables and window cleaning applications due to their ability to reach items when it is not practical to situate the machine directly underneath the issue. With a variety of joints allowing the machine to bend over or under items, the articulated boom lift is helpful for numerous applications. To enable operators to access many places, these sections of the boom lift can move independently. Articulated booms feature a tight turning radius, making them ideal for hallways and narrow storage corridors. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. These machines are often seen servicing overhead wires and power lines. Firefighters may use these machines and some articulated boom lifts have water cannons. Telescoping sections are available on certain models to extend reach to the maximum. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. Since these machines commonly work on steep ground and rough terrain, they resemble "spiders" with their long legs, and often go by that nickname on the job site. Smaller units called interior articulating boom lifts are capable of fitting through doorways, making them valuable in retail, warehousing and storage facilities. Electric models are preferred in interior situations due to the danger that carbon monoxide exhaust poses and how much quieter these models are. Telescopic Boom Lifts Designed otherwise, telescopic boom lift models bend differently from articulating boom lifts. These units use hydraulics to retract and extend outwards and upwards. The worker who is in the platform has the controls to extend the lift and is able to operate without a second worker. Some taller and larger models have a jib situated near the top that is similar to an articulating boom lift model. Boom lifts are available that reach higher than one-hundred and eighty feet. These machines are built to be stable and reliable. Some are able to extend to their full height capacity in less than 60 seconds. Adjustable speed, along with varying weight range capacities from 500 to 1000 lbs. are available in dual-fuel and diesel options. Available in 4WD and the ability to fit through small spaces. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib The jib is the extension found at the end of the main boom and between the platform. This design facilitates an extra hinge or articulation point to enable the platform to move up and down or horizontally. Articulating boom lifts and telescoping boom lifts may have jibs. There is an articulation point available on certain models situated halfway between the platform and the wheels to allow the machine to reach over an obstacle and be lowered again if needed. Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. In 1985, the first Genie Z-30/20 articulating Z-boom was introduced; their up-and-over capacity make them instantly popular and this design continues today. Proper Safety Measures Of course, safety is the highest priority when operating any

type of boom lift. All known safety hazards must be known to anyone working within the vicinity. Safely operating the equipment is a top priority for the operator and everyone in the working environment. Before operating the machine, effective communication and essential safety gear need to be in place. Prior to operating, ensure there are no open flames, combustible or flammable items, lit cigarettes, battery gases or engine fuels present. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. Maintaining a clear area around charging stations and work surfaces is important as tools or clutter could damage the boom lift or cause tire punctures etc. Daily Maintenance

Before engaging in activity, it is vital to do a visual inspection and consult the maintenance records to make sure all items are up to date and safe prior to operation. These industrial machines rely on lifting and supportive mechanisms to stabilize the weight. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. Single-use fasteners and components must not be reused as they may fail and become extremely dangerous. It is vital to discard oils and solvents safely and efficiently to prevent contaminating the environment. Adequate ventilation and lighting are essential in garages, workshops and along workbenches. Typically the wide umbrella of maintenance is distinguished by subsections such as Commissioning and Programmed Maintenance Intervals, Annual Maintenance, and Quarterly Maintenance.

Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Some of the maintenance categories for the boom lift include the Engine, Platform, Controls and Function, Turntable, Booms and Drive Chassis. Not complying with routine maintenance can put the operator at a huge safety risk, lead to damaged components, terrible performance and preventable downtime. The maintenance inspection report is an essential component to keeping the machine operable and the staff safe while extending the service life and overall performance of the machine. A list of single maintenance procedures that need to be conducted at 50-hour and 150-hour intervals is known as commissioning. There is quarterly and annual maintenance protocol that is conducted once or many times during the year. Programmed maintenance procedures are completed based on machine operating hours or during "pre-delivery" preparation. Consult your maintenance manual prior to operating to ensure all oil changes, battery life and fluid levels are primed for success.